



## TECHNICAL DATA SHEET

Product Name: **Foundation Coating**

Product #: 1701-D

Description: Black. Shiny. Water based. Non-fibered. Rubberized. Single component, easy to apply liquid that cures to form a water tight membrane. Formulated for heavy duty applications. Excellent adhesion on cured asphalt, metals, wood, aged concrete, EPS Insulation. Ready to use.



Uses: Foundation Sealant / Damp-proofer.

Directions: Mix pail. Apply to clean, dry, warm surface. Test small area before coating large area. Seal cracks greater than 1/8" with caulking or embedding geo-textile mesh between coats to cover cracks. Apply with brush or roller in 2-3 coats. Let material completely dry between coats. Allow 48 hours curing time before back filling. After each use, replace lid to keep material from drying in pail.  
Do not heat.  
Keep from freezing.

Coverage Rate: 1 gallon covers 30 s.f./ coat.

Clean - up: Clean tools with soap & water before dry.

Storage & Handling: Before handling, read product Safety Data Sheets and container labels for safe use for physical and health hazard information. Safety Data Sheets are available at [HerculesProducts.biz](http://HerculesProducts.biz).

Packaging: 5 gal pails: Approx. shipping weight 47 # / pail.

Typical Properties:
<b>Color:</b> Black
<b>Wt. / Gal:</b> 8.7 - 9.0
<b>Viscosity:</b> 6500-10000 Brookfield
<b>Solids by wt.:</b> 50-52
<b>Application Temp. F.:</b> 55-110
<b>Drying Time:Touch:</b> 70 deg. F., R.H. 50% - 6 hours
<b>Flash Point F.:</b> None
<b>pH:</b> 7.0 - 7.7
<b>VOC:</b> Zero

Hercules Products, Inc.  
6596 New Peachtree Rd.,  
Doraville, GA 30340  
[HerculesProducts.biz](http://HerculesProducts.biz)  
770-455-6531