



HERCULES

TECHNICAL DATA SHEET

Product Name: **White Commercial Roof Coating: Acrylic**

Product #: 1701-C

Description: Acrylic. White. Water Based.

Superior Exterior Durability.

Low toxicity & odor. Low V.O.C.

Non-flammable.

Dirt pick up resistance.

High reflectivity.

Highly flexible.



Ready to apply. Do not heat or thin.

Uses: Commercial roofs, RV's, Barns, Mobile Homes, Tractor Trailers. Excellent adhesion on cured asphalt, metals, TPO, Acrylic coatings, EPDM, PVC, Polyurethane foam, BUR, aged Concrete.

Directions: Mix pail. Apply to clean, dry, warm surface.

Brush, roll or spray on with 2-4 coats. Test small area for adhesion before coating large area. Allow at least 24 hours drying time between coats. After each use, replace lid to keep material from drying.

Coverage Rate: 1 gallon covers 70 s.f./coat.

Typical Properties:

Color: Bright White

Wt. / Gal: 12

Viscosity: 95 KU

Solids by wt.: 59%

Application Temp. F.: 55-110

Drying Time: Touch: 70 deg.

F., R.H. 50% - 2 hours.

Flash Point F.: None

pH: 8 - 10

Solar Reflectivity: 80 min.

VOC: < 50 g/l.

Tensile Strength: 300 psi

ASTM: D6083

Clean - up: Clean tools with soap and water before dry.

Storage & Handling: Before handling, read product Safety Data Sheets and container labels for safe use for physical and health hazard information. Safety Data Sheets are available at HerculesProducts.biz.

Hercules Products, Inc.

6596 New Peachtree Rd.,

Doraville, GA 30340

HerculesProducts.biz

770-455-6531

Packaging: 4.75 gal pail: Approx. shipping weight 59 # / pail.