



TECHNICAL DATA SHEET

Product Name: Black Anti-Skid Coating

Product #: 1701-B

Description: Black Anti-Skid Coating. Water based. Urethane modified polymers. Provides excellent safety enhancing slip resistant traction. Medium grit. Excellent adhesion to metals, concrete, stone, tile, cured asphalt, wood. Waterproofs.

Not for use on garage floors or areas for automobile traffic.
Keep from freezing.

Uses: Walkways, ramps, machinery operating areas, boat docks, steps, treads, patios, bleachers, etc.

Directions: Mix can. Make sure aggregate is thoroughly mixed before pouring. Apply to a clean, dry, warm surface with a brush or roller with 1 or 2 coats. Test small area before coating large area. Allow at least 4 hours drying time between coats. After each use, replace lid to keep material from drying in can.

Coverage Rate: 1 gallon covers 60 s.f. / coat.

Clean - up: Clean up tools with soap and water before dry.

Storage & Handling: Before handling, read product Safety Data Sheets and container labels for safe use for physical and health hazard information. Safety Data Sheets are available at HerculesProducts.biz.

Packaging: 1 gal can / case: Approx. shipping weight 12 # / case.



Typical Properties:
Color: Black
Wt. / Gal: 12.0#
Solids: 65%
Application Temp. F:55-110
Drying Time: Touch: 70 deg. F, R.H. 50% - 4 hours.
Flash Point F.: None
pH: 7.5 - 8.5
VOC: Zero

Hercules Products, Inc.
6596 New Peachtree Rd.,
Doraville, GA 30340
HerculesProducts.biz
770-455-6531