



TECHNICAL DATA SHEET

Product Name: White Commercial Roof Coating: Acrylic-Polyurethane Hybrid **Product #:** 1701-H

Description: Acrylic- Polyurethane Hybrid. White. Water Based.

Superior Exterior Durability.

Superior Toughness / Abrasion Resistance

Low toxicity & odor. Low V.O.C.

Non-flammable.

Dirt pick up resistance.

High reflectivity.

Highly flexible.

Water Ponding Resistance

Bleed & Stain resistance

Ready to apply. Do not heat or thin.

Uses: Commercial roofs, RV's, Barns, Mobile Homes, Tractor Trailers. Excellent adhesion on cured asphalt, metals, TPO, Acrylic coatings, EPDM, PVC, Polyurethane foam, BUR, aged Concrete.

Directions: Mix pail. Apply to clean, dry, warm surface. Brush, roll or spray on with 2-4 coats. Test small area for adhesion before coating large area. Allow at least 24 hours drying time between coats. After each use, replace lid to keep material from drying.

Coverage Rate: 1 gallon covers 80 s.f./coat.

Clean - up: Clean tools with soap and water before dry.

Storage & Handling: Before handling, read product Safety Data Sheets and container labels for safe use for physical and health hazard information. Safety Data Sheets are available at HerculesProducts.biz.

Packaging: 4.75 gal pail: Approx. shipping weight 59 # / pail.



Typical Properties:
Color: Bright White
Wt. / Gal: 10.5
Viscosity: 95 KU
Solids by wt.: 52%
Application Temp. F.: 55-110
Drying Time: Touch: 70 deg. F., R.H. 50% - 2 hours.
Flash Point F.: None
pH: 8.7-9.1
Solar Reflectivity: 80 min.
VOC: < 50 g/l.
Tensile Strength: 300 psi
ASTM:

Hercules Products, Inc.
6596 New Peachtree Rd.,
Doraville, GA 30340
HerculesProducts.biz
770-455-6531