



TECHNICAL DATA SHEET

Product Name: **White Commercial Roof Coating, S.B., SEBS:**

Product #: 1701-F

Description: SEBS. White. Solvent Based.

Flammable.

Superior Water Ponding Resistance.

Low V.O.C.

Dirt pick up resistance.

High reflectivity.

Highly flexible.



Ready to apply. Do not heat or thin.

Uses: Commercial roofs, Barns, Mobile Homes.

Excellent adhesion on metals, TPO, EPDM, PVC,

Polyurethane foam, aged Concrete.

Directions: Mix pail. Apply to clean, dry, warm surface.

Brush, roll or spray on with 2-3 heavy coats. Test small area for adhesion & bleeding before coating large area. Allow at least 2 hours drying time between coats. After each use, replace lid to keep material from drying.

Coverage Rate: 1 gallon covers 60 s.f./coat.

Clean - up: Clean tools with mineral spirits.

Storage & Handling: Before handling, read product Safety Data Sheets and container labels for safe use for physical and health hazard information. Safety Data Sheets are available at HerculesProducts.biz.

Packaging: 5 gal pail: Approx. shipping weight 50.5# / pail.

Typical Properties:
Color: White
Wt. / Gal: 9.1
Viscosity: 11,300 cps
Solids by wt.: 50%
Application Temp. F.: 55-110
Drying Time: Touch: 70 deg. F., R.H. 50% - 2 hours.
Flash Point F.:
pH: 8 - 10
Solar Reflectivity: 80 min.
VOC:
Tensile Strength: 2081 psi
ASTM: D6043

Hercules Products, Inc.
6596 New Peachtree Rd.,
Doraville, GA 30340
HerculesProducts.biz
770-455-6531